

FIREWORLD

Maintenance Free Fire Extinguisher P50F – AFFF foam



The Aqueous Film Forming Foam (AFFF) additive is a blend of perfluorinated and hydrocarbon surfactants. It enables the formation of an aqueous film capable of spreading on the surface of burning fuels, which prevents vapour production and seals the surface from oxygen.

This model has passed the requirements of EN3 for the suitability of being used on live electrical equipment.

AFFF will extinguish class A (carbonaceous) fires and class B (flammable liquid) fires.

key points

- Approved and certified to EN3
- CE marked in accordance with the PED
- 10 year manufacturer's warranty
- 10 year service free life
- Manufactured in Great Britain
- Reliable super strength composite material
- Designed for long service in harsh conditions
- No risk of corrosion
- Fire rating 27A/183B
- No split/dropped lining
- 100% recyclable
- Carbon neutral benefits
- 100% UV protected



Technical Specification

Model	Capacity (litres)	Fire rating	Full Weight (Kgs)	Temp Range	Operating pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Diameter (mm)	Height (mm)
P50F	6	27A/183B	8.5	+5°C to +60°C	12	40	4	178	570

Britannia Fire reserve the right to alter the specification of the product without prior notice



www.Britannia-Fire.co.uk